



ZOTEFOAMS

Zotefoams plc

675 Mitcham Road
Croydon
CR9 3AL
UK

t +44 (0)20 8664 1600
f +44 (0)20 8664 1616
e info@zotefoams.com
www.zotefoams.com

December 2023

OFFICIAL STATEMENT

**STATE OF CALIFORNIA
ENVIRONMENTAL PROTECTION AGENCY
OFFICE OF ENVIRONMENTAL HEALTH HAZARD ASSESSMENT
SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT OF 1986
CHEMICALS KNOWN TO THE STATE TO CAUSE CANCER OR REPRODUCTIVE
TOXICITY
(‘Proposition 65’)**

This is to confirm the status of the foam used in T-FIT® Hygiene, ZOTEK® F43 HT, regarding the use of substances listed in the California Proposition 65 list dated August 11th 2023. This statement covers the foam used in T-FIT® Hygiene products listed in Table 1 and Table 2.

We can confirm that none of the substances listed in ‘Proposition 65’ are used or otherwise intentionally added during the current foam manufacturing process employed by Zotefoams plc for the production of our foam products stated above.

It is important to note that this statement applies to the T-FIT products as they leave Zotefoams production facilities. Zotefoams will not accept liability for other materials or processes used in combination with T-FIT products.

We trust that the above statement is sufficient, however if any further information or clarification is required then please do not hesitate to contact the Technical Support group at the web address above.

Yours sincerely,

**Dr Karl Hewson
Director of Technology and Development**



ZOTEFOAMS

Table 1: List of T-FIT® Hygiene Products in 6.35 mm thickness

Product Code	T-FIT® Hygiene Moulded from Zotek®F43HT, product length 960mm	Product Internal Diameter	
		Imperial	Metric mm
TFHS012A06U000-9001	ASME BPE 0.5" OD 12.7MM T-FIT Hygiene Insulating Straight 6.35mm THK	0.5"	12.7
TFHS019A06U000-9002	ASME BPE 0.75" OD 19.0MM T-FIT Hygiene Insulating Straight 6.35mm THK	0.75"	19
TFHS025A06U000-9003	ASME BPE 1.0" OD 25.40mm T-FIT Hygiene Insulating Straight 6.35mm THK	1"	25.4
TFHS038A06U000-9004	ASME BPE 1.5" OD 38.10mm T-FIT Hygiene Insulating Straight 6.35mm THK	1.5"	38.1
TFHS050A06U000-9005	ASME BPE 2.0" OD 50.80mm T-FIT Hygiene Insulating Straight 6.35mm THK	2"	50.8
TFHS063A06U000-9006	ASME BPE 2.5" OD 63.50mm T-FIT Hygiene Insulating Straight 6.35mm THK	2.5"	63.5
TFHS076A06U000-9007	ASME BPE 3.0" OD 76.20mm T-FIT Hygiene Insulating Straight 6.35mm THK	3"	76.2
TFHS101A06U000-9008	ASME BPE 4.0" OD 101.60mm T-FIT Hygiene Insulating Straight 6.35mm THK	4"	101.6
TFHS021I06U000-9009	ISO 1127 DN15 OD 21.3mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN15	21.3
TFHS026I06U000-9010	ISO 1127 DN20 OD 26.9mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN20	26.9
TFHS033I06U000-9011	ISO 1127 DN25 OD 33.7mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN25	33.7
TFHS042I06U000-9017	ISO 1127 DN32 OD 42.4mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN32	42.4
TFHS048I06U000-9012	ISO 1127 DN40 OD 48.3mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN40	48.3
TFHS060I06U000-9013	ISO 1127 DN50 OD 60.3mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN50	60.3
TFHS076I06U000-9014	ISO 1127 DN65 OD 76.1mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN65	76.1
TFHS088I06U000-9015	ISO 1127 DN80 OD 88.9mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN80	88.9
TFHS114I06U000-9016	ISO 1127 DN100 OD 114.3mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN100	114.3
TFHS023D06U000-9004	DIN 11850 DN20 OD 23.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN20	23
TFHS029D06U000-9005	DIN 11850 DN25 OD 29.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN25	29
TFHS035D06U000-9006	DIN 11850 DN32 OD 35.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN32	35
TFHS041D06U000-9007	DIN 11850 DN40 OD 41.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN40	41
TFHS053D06U000-9008	DIN 11850 DN50 OD 53.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN50	53
TFHS070D06U000-9009	DIN 11850 DN65 OD 70.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN65	70
TFHS085D06U000-9010	DIN 11850 DN80 OD 85.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN80	85
TFHS104D06U000-9011	DIN 11850 DN100 OD 104.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	DN100	104
TFHS057G06U000-9006	GB 12459 2.0" OD57.00mm T-FIT Hygiene Insulating Straight 6.35mm THK	2.0"	57





ZOTEFOAMS

Table 2: List of T-FIT Hygiene Products in 12.7 mm thickness

Product Code	T-FIT® Hygiene Moulded from Zotek®F43HT, product length 960mm	Product Internal Diameter	
		Imperial	Metric mm
TFHS025A12U000-9003	ASME BPE 1.0" OD 25.40mm T-FIT Hygiene Insulating Straight 12.70mm THK	1"	25.4
TFHS038A12U000-9004	ASME BPE 1.5" OD 38.10mm T-FIT Hygiene Insulating Straight 12.70mm THK	1.5"	38.1
TFHS050A12U000-9005	ASME BPE 2.0" OD 50.80mm T-FIT Hygiene Insulating Straight 12.70mm THK	2"	50.8
TFHS063A12U000-9006	ASME BPE 2.5" OD 63.50mm T-FIT Hygiene Insulating Straight 12.70mm THK	2.5"	63.5
TFHS076A12U000-9007	ASME BPE 3.0" OD 76.20mm T-FIT Hygiene Insulating Straight 12.70mm THK	3"	76.2
TFHS101A12U000-9008	ASME BPE 4.0" OD 101.60mm T-FIT Hygiene Insulating Straight 12.70mm THK	4"	101.6
TFHS021I12U000-9009	ISO 1127 DN15 OD 21.3mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN15	21.3
TFHS026I12U000-9010	ISO 1127 DN20 OD 26.9mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN20	26.9
TFHS033I12U000-9011	ISO 1127 DN25 OD 33.7mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN25	33.7
TFHS042I12U000-9017	ISO 1127 DN32 OD 42.4mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN32	42.4
TFHS048I12U000-9012	ISO 1127 DN40 OD 48.3mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN40	48.3
TFHS060I12U000-9013	ISO 1127 DN50 OD 60.3mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN50	60.3
TFHS076I12U000-9014	ISO 1127 DN65 OD 76.1mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN65	76.1
TFHS088I12U000-9015	ISO 1127 DN80 OD 88.9mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN80	88.9
TFHS023D12U000-9004	DIN 11850 DN20 OD 23.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN20	23
TFHS029D12U000-9005	DIN 11850 DN25 OD 29.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN25	29
TFHS035D12U000-9006	DIN 11850 DN32 OD 35.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN32	35
TFHS041D12U000-9007	DIN 11850 DN40 OD 41.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN40	41
TFHS053D12U000-9008	DIN 11850 DN50 OD 53.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN50	53
TFHS070D12U000-9009	DIN 11850 DN65 OD 70.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN65	70
TFHS085D12U000-9010	DIN 11850 DN80 OD 85.00mm T-FIT Hygiene Insulating Straight 12.7mm THK	DN80	85

